



10.4" Rimless POS LCD Monitor



New Capacitive Touch keys control design provide high durability of operation, also with a thin & whole flat front panel gives an elegant and compact appearance.

Features

1. Rimless front bezel design, spill & dust proof, meets IP54 requirement
2. Low power consumption only 6W with LED backlight
3. Cable cover to prevent unexpected pull from users
4. Sleek surface throughout monitor's appearance
5. Viewing angle adjustment up to 68°
6. Universal power brick with changeable plug
7. VESA 75 x 75 mm wall mounting standard
8. User friendly OSD control buttons
9. Integrated protection glass
10. Smart cable management
11. Small footprint



Specification

Model	P104VG
Cabinet Color	Black or White
Cover Lens	Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93%
Display Type	10.4" diagonal TFT active matrix with LED backlight
Recommended Resolution	800 x 600
Brightness	300 cd/m ² (typ.)
Contrast Ratio	500:1 (typ.)
Viewing Angle	110° (H) / 150° (V)
I/O Connectivity	D-sub 15 pins, DC 12V
Backlight MTBF	10,000 hrs / 30,000 hrs (option)

* Specification is subject to be changed without prior notice.


Application

Supermarket / Chain stores / Hospitality / Factory automation

Universal power plug



I/O indication



Dimension (unit: mm)

